MUNICIPAL & UNIVERSITY STORMWATER PROGRAM PARTNERSHIP

LEXINGTON MASSACHUSETTS

UNIVERSITY of MASSACHUSETTS LOWELL









CREATING A UNIVERSITY IDDE PROGRAM



UNIVERSITY STUDENTS







Prof. Edward L. Hajduk, D.Eng, PE
Faculty Advisor
UMass Lowell ASCE Student Chapter









CREATING A UNIVERSITY IDDE PROGRAM



INTERN CLASSROOM TRAINING SESSION AT LEXINGTON DPW







CREATING A UNIVERSITY IDDE PROGRAM

Safety Training is an important part of the program from the beginning


- Always work in teams
- Safety lesson on working near water
- Tick education
- Emergency protocol training





MANAGING A UNIVERSITY IDDE PROGRAM

INTERN FIELD BINDER WITH DETAILED SAMPLING INSTRUCTIONS



BINDER ALSO HAS OUTFALL PHOTO, OUTFALL MAPS, DATA SHEETS AND LETTER FROM TOWN

Ammonia and Chlorine Water Quality Sampling Protocol Lexington Watershed Stewardship Program Revised January 2, 2014

Step 1. Collect water sample

- Select a sample location as close to the pipe as possible.
- Submerge dipper 6 inches below water surface (if possible) to fill dipper, then pour out water on bank. This is to rinse the dipper.
- . Submerge dipper 6 inches below water surface again to retrieve sample.
- Place filled dipper on bank or in a convenient location for conducting tests.



Step 2. Take water temperature

- As soon as possible, take temperature of sample in dipper by inserting temperature probe into water and holding until steady temperature reading
- Record temperature on data sheet in degrees




8

INTERN SAMPLING PROTOCOL






MANAGING A UNIVERSITY IDDE PROGRAM



OUTFALL PHOTO







MANAGING A UNIVERSITY IDDE PROGRAM



Town of Lexington
Department of Public Works
Engineering

John R. Livsey, P.E. Town Engineer Tel: (781) 274-8305 Fax: (781) 274-8385

Dear Neighbor,

Interns working with the Lexington Engineering Division are conducting water quality sampling to help improve stornwater quality in Lexington. Teams are made up of 2 or more students from the University of Massachusetts at Lowell (UML). The UML stream teams will take water samples from pipes that drain into our brooks and streams. This program is vital in our efforts to clean up the streams and brooks of Lexington. At times, these interns need to access drainage easements to evaluate discharge into streams. This may entail passing by or through your land.

If you have concerns, please contact:

Dave Pavlik Town of Lexington Engineering Division 201 Bedford Street Lexington, MA 02420 781.274.8309 dpavlik@lexingtonma.gov

John R. Livsey, P.E. Town Engineer



OFFICIAL LETTER AND ID BADGES

201 BEDFORD STREET *SAMUEL HADLEY PUBLIC SERVICES BUILDING * LEXINGTON, MASSACHUSETTS 02420





TASKS OF A UNIVERSITY IDDE PROGRAM



OUTFALL RECONNAISSANCE & INVENTORY

UMASS LOWELL STREAM TEAM

Section 1: Background Data

| Sub watershed: Vine Brook | Outfall ID: OF 14-2 |
|---------------------------|------------------------------------|
| Today's Date: 5/12/14 | Time: 1015 |
| Investigators: DP, JL | Form Completed by: DP |
| Temperature (Air): 67 | Rainfall (in.) last 24 hours: 0.12 |

Section 2: Photo Inventory
Photo of Outfall taken:

YES

NO

If yes email to stormwater@lexingtonma.gov If no, why no photo?

Section 3: Outfall Description - Pick one type (a or b), then circle appropriate descriptors.

| oconon o. Outlan De. | Scription - Fick one type (a or b), | | , tricii olioic | | | | |
|----------------------|-------------------------------------|---------------|-----------------|--------|--------------|-----------|--------------|
| Type | Mater | ial | Sh | ape | Diame | ter (IN.) | Submerged |
| | Concrete | Corrugated | Circular | Single | 4 | 24 | In Water: |
| a. Closed Pipe | Plastic | Metal | Elliptical | Double | 6 | 36 | No |
| | Steel | Black Plastic | Box | Triple | 8 | 48 | Partially |
| | | | | | 12 | 72 | Fully |
| | Other: | | Other: | Other: | 18 | Other | |
| | Concr | ete | Trap | ezoid | Depth: | | In Sediment: |
| b. Open drainage | Earth | en | Para | bolic | | | No |
| | Rip-R | lap | Natural c | hannel | Top Width: | | Partially |
| | Other: | | Other: | | Bottom Width | h: | Fully |

Section 4: Water Flow Parameters

| Flow Present? | Yes | No | |
|------------------|---------|----------|-------------|
| Flow Description | Trickle | Moderate | Substantial |
| (If Present) | | | |

Section 5: Water Quality Parameters

| | | - | | | | | | |
|-----------|--------------|---------------|---------------|-------------|--------------|---------------------------|---------------------------------|---------------------|
| Time | Clarity | Color | Odor | Temp (F°) * | DO (mg/l)* | SP Cond*(µmh os/cm) | Ammonia test strip (mg/l) | Samples for lab† |
| 1030 | Clear | Clear | None | 58 | 8.5 | 750 | 0.25 | E,A,S |
| | | Water Quality | Parameters to | be used for | discription | in above colu | ımn | |
| Clarity | | Clear | Cloudy | | | | | |
| Color | | Clear | Gray | Light Tea | Light Green | Tea | White | Other |
| Odor | | None | Musty | Fishy | Oily | Organic | Sewage | Rotten Eggs |
| amples fo | or the lab A | bbreviations | | | | | | |
| A=Ammor | E = Ecoli, | S=Surfactant, | FC = Fecal Co | liform, | TP = Total P | hosphorus, | | |
| *Record V | alues from \ | /SI meter | | | | | | |

Section 6: Comments





TASKS OF A UNIVERSITY IDDE PROGRAM

TOWN OF LEXINGTON

SAMPLE COLLECTION DATA SHEET

UMASS LOWELL STREAM TEAM

| Sub watershed: Vine brook | Date: 6/5/14 | Investigators: DP,MS |
|---------------------------|-----------------------------------|-----------------------|
| Temperature (Air)-F°: 70 | Rainfall (in.) last 24 hours: 0.2 | Form Completed by: MS |

| SAMPLE LOCATION: | Time | Flow Present? (Y/N) | Flow Description | Clarity | Color | Odor | Temp (F) * | DO (mg/l)* | SP Cond*(µm hos/cm) | Chlorine× | Ammonia test strip (mg/l) | Samples for lab† |
|---------------------|------|---------------------------|---------------------|---------|-------|------|------------|------------|---------------------------|-----------|---------------------------------|------------------|
| OF 15-30 | 1030 | Υ | Moderate | Clear | Clear | None | 68 | 8.56 | 750 | 0.03 | 0.25 | E,A,S |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

Key for data collection

| Water Flow | Parameters | to be used a | bove |
|------------------|------------|--------------|-------------|
| Flow Present? | Yes | No | |
| Flow Description | Trickle | Moderate | Substantial |

| †Sampl | es for the lab Abbreviatio | ns to be used above |
|-----------|----------------------------|---------------------|
| E = Ecoli | FC = Fecal Coliform | A=Ammonia |
| TP= | Total Phosphorus | S=Surfactant |

| | | Water Qua | ality Par | ameters to be | used above | | | |
|---------|-------|-----------|-----------|---------------|------------|--------|-------------|-------|
| Clarity | Clear | Cloudy | | | | | | |
| Color | Clear | Grey | Tea | Light Green | White | Other | | |
| Odor | None | Musty | Fishy | Oily | Organic | Sewage | Rotten Eggs | Other |

*Record Values from YSI meter for Temp, DO & Conductivity *Record number from colorimeter

| Comments or unusual flow observations | |
|---------------------------------------|--|
| | |





TIME COMMITMENTS FOR A UNIVERSITY IDDE PROGRAM



PROGRAM KICK OFF WITH A TWO HOUR TRAINING SESSION





TIME COMMITMENT FOR A UNIVERSITY IDDE PROGRAM

Program management

- Work closely with student project manager
- Preparation time for restocking kit
- Preparation time for sample bottles
- Coordinating field work with students and lab
- Time commitment for quality assurance of work





TIME COMMITMENTS FOR A UNIVERSITY IDDE PROGRAM

Program results

- Work with students sharing data to online spreadsheet
- Analysis of data
- Evaluation of outfall data





TIME COMMITMENT FOR A UNIVERSITY IDDE **PROGRAM**

Classroom and field refresher training





REFRESHER TRAINING SESSION AT UNIVERSITY PROGRAM IMPROVEMENTS & FIELD TRAINING





FINANCIAL COMMITMENT OF A UNIVERSITY IDDE PROGRAM







FINANCIAL COMMITMENT OF A UNIVERSITY IDDE PROGRAM

ECOLI






SURFACTANTS





AMMONIA









FINANCIAL COMMITMENT OF A UNIVERSITY IDDE PROGRAM









MULTIMETER FOR SAMPLING



TAKING MEASUREMENTS AND STORING DATA WITH THE YSI

- Press to turn the instrument on. The instrument will be in Run mode and begin sampling but not recording.
- To begin recording, insert the entire probe past the orange marker. Shake the probe in the sample to release any air bubbles and wait until the temperature and DO stabilize. The YSI will beep and the AS symbol next to the DO readings will be solid once it has stabilized.
- 3. To begin recording data on the YSI, highlight Log One Sample and press ENTER. Log One Sample is already highlighted when the instrument is turned on. A submenu will open at the top of the screen. Highlight Sites and press ENTER. Select the outfall to be sampled and press ENTER. Then highlight Folders and select the subwatershed and press ENTER.
- Then highlight Log Now and press ENTER. If there is no flow, gently move the probe in a stirring motion to provide movement for measuring DO.
- The instrument will confirm that the data point was logged successfully on the YSI, with a beep and solid AS symbol next to the DO and SPC readings.
- 6. Record the Temp. (°F), DO (mg/L), and Conductivity (μS/cm) on the Sample Collection data sheet.
- Once sampling is complete remove the probe from the water and turn off the instrument. Then lightly shake off the probe to remove excess water. Place the transport sleeve over the probe and return the instrument to the carrying case.

MULTIMETER INSTRUCTION PROVIDED WITH INTERN BINDER





FINANCIAL COMMITMENT OF A UNIVERSITY IDDE PROGRAM



Chlorine

COLORIMETER FOR CHLORINE





- 1. Press and hold until colorimeter turns on.
- 2. Press ENTED to select TESTING MENU.
- 3. Select ALL TESTS (or another sequence containing 014 Chlorine) from TESTING MENU.
- 4. Scroll to and select 014 Chlorine from menu.
- 5. Rinse a clean tube (0290) with sample water. Fill to the 10 mL line with sample
- 6. Insert tube into chamber, close lid and select SCAN BLANK
- 7. Remove tube from colorimeter. Add one *Chlorine DPD #1 Instrument Grade Tablet (6903A). Cap tube and shake for 10 seconds. Invert slowly 5 times. Solution will turn pink if free chlorine is present
- 8. Immediately insert tube into chamber, close lid and select SCAN SAMPLE.

Procedure for Combined Chlorine

- 9. Add one Chlorine DPD #3 instrument grade tablet to sample from step 8 above. Cap tube and shake for 10 seconds. Invert slowly 5 times. An increase in color represents combined chlorine.
- 10. Insert sample into chamber, close lid and select SCAN SAMPLE. Record result as Total Chlorine.
- 11. You can subtract free chlorine from total chlorine readings to obtain concentration of combined
- 12. Press to turn off the colorimeter

COLORIMETER TESTING INSTRUCTION PROVIDED WITH INTERN BINDER



BENEFITS TO A UNIVERSITY IDDE PROGRAM

Benefits to the municipality

- Public outreach credit for your MS4 permit
- IDDE Compliance for your MS4 permit
- Improved water quality in your community
- Community recognition
- Opportunity to give back to future engineers





BENEFITS TO A UNIVERSITY IDDE PROGRAM

Benefits to students

- Exposure to Environmental Issues
- Hands on experience
- Professional Development
- Networking Opportunities
 - With Professionals
 - With other Students
- Internship opportunities
- Learning to work with Professional Engineers and other students in a team
- Community Service Experience



STREAM TEAM MEMBERS WORKING ON OUTFALL INVENTORY IN MILL BROOK





LATEST IMPROVEMENTS AND FUTURE ASPIRATIONS

- Increase student involvement
- Expand testing parameters
- Acquire new equipment
- Lab tours
- Expansion to other nearby communities (e.g. Woburn)
- Spread awareness of the need for developing municipal partnerships for IDDE programs



STREAM TEAM MEMBERS USING COLORIMETER AT OUTFALL SAMPLING IN VINE BROOK





SUCCESS OF PROGRAM

- "STORMY" Award- Best
 Stormwater Idea in New
 England at the Spring 2015
 NEWWA Conference
- The "STORMY" Award is given by the New England Stormwater Collaborative and recognizes simple, imaginative, and inventive ways that New England communities are increasing staff capacity, funding, or political support for stormwater management programs.



STORMY ACCETANCE





SUCCESS OF PROGRAM

- BEST POSTER AWARD- UMass Lowell Undergraduate Research Symposium
- Created, printed, and presented a poster about the Town of Lexington Stormwater Monitoring Project to a panel of judges
- One of 4 posters selected for the award from the College of Engineering



POSTER PRESENTATION





SUCCESS OF PROGRAM

- OUTSTANDING COMMUNITY
 SERVICE AWARD to the UMass
 Lowell ASCE Student Chapter
 out of all Student Organizations
 at the University
- Students at UMass Lowell sent in written submissions that were reviewed by judges
- The Town of Lexington
 Stormwater Monitoring Project
 is one of four community service
 projects that the UML ASCE club
 runs



COMMUNITY SERVICE AWARD







CITY OF WOBURN MS-4 STORMWATER MANAGEMENT PROGRAM

PROJECT MANAGERS: REBECCA GONSALVES-LAMONTAGNE & STEPHANIE COLLINS

CITY ENGINEER: JOHN E. COREY, JR. P.E.

TRIBUTARY AREA DELINEATION



Contours at Horn Pond

- Students will learn the basics of contour mapping and then use the contour lines to determine drainage areas
- All work will be checked by city engineers to assure accuracy

 Teams will work in one drainage area at a time, moving onto the next once all testing is completed in the first area and if city engineers feel a sufficient number of data points have been collected

DRAINAGE SYSTEM CONNECTIVITY




Connected Drainage



Unconnected Drainage

- PeopleGIS allows for quick and accurate mapping of the drainage system
- Drainage will be connected using information in the Engineering office



OUTFALL AND DRAINAGE MAPPING


Google Hybrid Map Google Terrain Mar

• Drainage and outfalls can be mapped in the field as they are discovered

 City Engineers can monitor the upda to the map in real-time

PeopleGIS provides an interactive missewer Syste accessible to anyone and found at:
 www.mapsonline.net/woburnma/index

• This also assists the city with cleanu 2013 ortho Basen and repairs to the drainage system as this information will continually be updated over the life of the program





City of Woburn's PeopleGIS Stormwater homepage



surfactants, salinity and temperat All testing results, outfall photos, and

| er Quality Field Screening Form |
|---------------------------------|
| CREENING |
| oonia |
| n |
| ride |
| r |
| ific Conductance |
| rgents & Surfactants |
| ride |
| ness |
| |
| ssium |
| idity |
| nents: |
| erature: 59.4°F |
| |





Chapter 11: Outfall Reconnaissance Inventory



LABORATORY TESTING

Students will learn and perform the following:

- E. coli and 5 day BOD tests in the lab at the Woburn Water Treatment Plant
- pH test with the Hach probe and Phete Colilert EPA approved 24 hour test for *E. coli* in the city's non-distressed waters





Woburn Water Treatment Plant & Laboratory




Colorimeter and Hach Probes



Colilert sample bottles & trays`





From "Evaluating the Effectiveness of Municipal Stormwater Programs", EPA January 2008

- Improve public outreach
- Adapt to new drafts of the permit quickly
- Introduce more students to stormwater management
 and Illicit Discharge Detection and Elimination P
- Work toward getting students school credit hor participating in the program
- Continually evaluate and modify the program to insure its success and effectiveness
- Assist Lexington in spreading this program to communities

MUNICIPAL & UNIVERSITY STORMWATER PROGRAM PARTNERSHIP

Thank you for your interest in our program

We now have time for your questions





